

EcoPLAT

|FRD.



EcoPLATbase
EcoPLAT

|PPS.



EcoPLAT

|RS.



EcoPLAT



EcoPLAT

BRETTAVAFNINGSVÉLAR MEÐ SNÚNINGSPALLI

TURNTABLE STRETCH WRAPPING MACHINES

TÆKNILEGAR UPPLÝSINGAR	ECOPLAT BASE	ECOPLAT	ECOPLATTP
Þvermál snúningspalls	1500 mm	1500-1650 mm	1500 mm
Mesta þyngd	1200 Kg	2000 kg	1200 Kg
Mesta hæð á bretti	2200 mm	2200 mm	2200 mm
Bremsu / strekkibúnaður	FRD	FRD, RS, PPS	FRD, RS, PPS
Breytilegur snúningshraði	10RPM	from 4 to 10 RPM	from 4 to 10 RPM
Breytilegur hraði í færslu á filmu	3.6 mt/min	from 1 to 4 mt/min	from 1 to 4 mt/min
Rafmagn	230 1 PH (±20%)VAC	230 1 PH (±20%)VAC	230 1 PH (±20%)VAC
Raftíðni	50/60 Hz	50/60 Hz	50/60 Hz



SAMHENTIR
UMBÚÐALAUSNIR

We pack your business!

www.aetnagroup.com

ROBOPAC